



CITEL

1-pair DIN rail plug-in Data surge protector

DLA-06D2/R



- High current data transmission
- Common mode and differential mode protection
- Data lines, including those isolated from Earth
- Compact DIN rail enclosure, high density protection
- Protection of shield wire
- Location and test categories: D1, C2, C3
- IEC 61643-21 compliance



	Electrical Characteristics																										
<table border="1"> <tr><td>Network</td><td>RS422, RS485</td></tr> <tr><td>Nominal line voltage</td><td>Un 6 V</td></tr> <tr><td>Max. DC operating voltage</td><td>Uc 8 Vdc</td></tr> <tr><td>Cut-off frequency -3dB, 100 ohm system</td><td>f max. > 75 MHz</td></tr> <tr><td>Cut-off frequency -1dB, 100 ohm system</td><td>f max. > 30 MHz</td></tr> <tr><td>Max. load current @25°C</td><td>IL 600 mA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 μs by pole</td><td>Imax 20 kA</td></tr> <tr><td>Nominal discharge current C2 Category</td><td>In 10 kA</td></tr> <tr><td>Protection Level C3 (10/1000μs), 300 applications@10 A, Y-Y (Line/Line)</td><td>Up 30 V</td></tr> <tr><td>Protection Level C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)</td><td>Up 650 V</td></tr> <tr><td>Max. capacitance</td><td>C < 50 pF</td></tr> <tr><td>Impulse current D1 (10/350μs), 2 applications, X-C (Line/Earth)</td><td>limp 5 kA</td></tr> <tr><td>Line resistance (± 10%)</td><td>2 Ohm</td></tr> </table>	Network	RS422, RS485	Nominal line voltage	Un 6 V	Max. DC operating voltage	Uc 8 Vdc	Cut-off frequency -3dB, 100 ohm system	f max. > 75 MHz	Cut-off frequency -1dB, 100 ohm system	f max. > 30 MHz	Max. load current @25°C	IL 600 mA	Max. discharge current max. withstand @ 8/20 μs by pole	Imax 20 kA	Nominal discharge current C2 Category	In 10 kA	Protection Level C3 (10/1000μs), 300 applications@10 A, Y-Y (Line/Line)	Up 30 V	Protection Level C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)	Up 650 V	Max. capacitance	C < 50 pF	Impulse current D1 (10/350μs), 2 applications, X-C (Line/Earth)	limp 5 kA	Line resistance (± 10%)	2 Ohm	Mechanical Characteristics
Network	RS422, RS485																										
Nominal line voltage	Un 6 V																										
Max. DC operating voltage	Uc 8 Vdc																										
Cut-off frequency -3dB, 100 ohm system	f max. > 75 MHz																										
Cut-off frequency -1dB, 100 ohm system	f max. > 30 MHz																										
Max. load current @25°C	IL 600 mA																										
Max. discharge current max. withstand @ 8/20 μs by pole	Imax 20 kA																										
Nominal discharge current C2 Category	In 10 kA																										
Protection Level C3 (10/1000μs), 300 applications@10 A, Y-Y (Line/Line)	Up 30 V																										
Protection Level C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)	Up 650 V																										
Max. capacitance	C < 50 pF																										
Impulse current D1 (10/350μs), 2 applications, X-C (Line/Earth)	limp 5 kA																										
Line resistance (± 10%)	2 Ohm																										
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr><td>Technology</td><td>GDT+TVS diode</td></tr> <tr><td>SPD configuration</td><td>1-pair+shielded</td></tr> <tr><td>Connection to Network</td><td>Spring terminal: cross section 0.5-2.5mm²</td></tr> <tr><td>Format</td><td>Din Rail Base-Plug-in Module</td></tr> <tr><td>Mounting</td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating and storage temperature</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td>Short-circuit</td></tr> <tr><td>Disconnection indicator</td><td>Transmission interrupt - default mode 2</td></tr> <tr><td>Spare module(s)</td><td>DLAM-06D2</td></tr> <tr><td>Dimensions</td><td>See diagram</td></tr> </table>	Technology	GDT+TVS diode	SPD configuration	1-pair+shielded	Connection to Network	Spring terminal: cross section 0.5-2.5mm ²	Format	Din Rail Base-Plug-in Module	Mounting	Symmetrical rail 35 mm (EN 60715)	Housing material	Thermoplastic UL94 V-0	Operating and storage temperature	-40/+85°C	Protection rating	IP20	Failsafe mode	Short-circuit	Disconnection indicator	Transmission interrupt - default mode 2	Spare module(s)	DLAM-06D2	Dimensions	See diagram		
Technology	GDT+TVS diode																										
SPD configuration	1-pair+shielded																										
Connection to Network	Spring terminal: cross section 0.5-2.5mm ²																										
Format	Din Rail Base-Plug-in Module																										
Mounting	Symmetrical rail 35 mm (EN 60715)																										
Housing material	Thermoplastic UL94 V-0																										
Operating and storage temperature	-40/+85°C																										
Protection rating	IP20																										
Failsafe mode	Short-circuit																										
Disconnection indicator	Transmission interrupt - default mode 2																										
Spare module(s)	DLAM-06D2																										
Dimensions	See diagram																										
Standards	Standards compliance																										
Part number	6401612																										

